

Bayley Double Extension Ladder

Our products are specifically designed to meet the demanding requirements of Fire and Rescue services.

Bayley DX ladders range from 3.9m up to 10.5m, in 2 section configuration, the swaged rung and box section construction provides a ladder that is both robust and durable.

Design & Construction

A lighter weight box stile section with fully ribbed surface for better grip with large diameter rungs swaged in place.

Options offered are dependent on ladder type and size and have twin independent automatic pawls, automatic arrest device and wall wheels.

The ladders are manufactured from high tensile aluminium alloy custom extrusions giving high strength and rigidity.

Specifications & Use

We build our ladders to the BS EN1147:2010 standard. Bayley ladders are the mainstay of Fire & Rescue Services both nationally and internationally.



Bayley Double Extension Ladder

BAYLEY double extension ladders						
Model	BL19-10E	BL19-11E	BL19-25E	BL19-15E	BL19-16E	BL19-14E
Length Extended	3.9m	4.5m	5.4m	7.3m	9.16m	10.5m
Length closed	2.44m	2.7m	3.4m	4.5m	5.48m	6.5m
width overall	352mm	352mm	352mm	450mm	450mm	450mm
Depth	125mm	125mm	118mm	170mm	170mm	170mm
Weight	15.5kg (34.5lbs)	18kg (40lbs)	22kg (49lbs)	30kg (67lbs)	38kg (85lbs)	48kg (107lbs)
EN 1147 Categorisation	3 person rescue	3 person rescue	3 person rescue	3 person rescue	3 person rescue	3 person rescue